## REMARKS

Both claims 20 Mark have been amended to delete the phrase "said support means extending in a direction substantially parallel to said longitudinal axis of said elongated member."

The applicant respectfully thanks the Examiner for pointing out the bone fide mistake in failing to delete this phrase and for allowing further amendment of the claims.

Respectfully submitted,

JACKSON WALKER L.L.P.

Thomás E. Sisson Reg. No. 29,348

1.12 E. Pecan Street, Suite 2100 San Antonio, Texas 78205

Telephone: (210) 978-7700 Fax: (210) 978-7790 Attorneys for Applicant JUN 13 2001
TECHNOLOGY CENTER 3700

## **CERTIFICATE OF MAILING**

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited on the date shown below with the United States Postal Service, with sufficient postage as First Class Mail (37 CFR 1.8(a)), in an envelope addressed to Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Date: June 7, 2001

Bianca Grossweiler

2619153.1

## VERSION WITH MARKINGS TO SHOW CHANGES MADE

## In the Claims:

26. (Twice Amended) A cold separation device for separating a cold elongate metallic member along a substantially longitudinal axis thereof, said device comprising:

a separation unit having a cutter;

support means extending upstream and downstream of said separation unit to support said elongate member[, said support means extending in a direction substantially parallel to said longitudinal axis of said elongated member];

a feeder means to feed said elongate member towards and through said separation unit, said feeder means further comprising a pusher arm upstream of said separation unit, said pusher arm exerting a force on an end of said elongate metallic member distal from said separation unit to push said member towards and through the said separation unit; and

means to constrain lateral movement of said elongate metallic member passing through said separation unit said constraining means further comprising at least one pair of horizontally spaced apart guide rollers, said guide rollers being freely rotatable about a substantially vertical axis, wherein downstream of said separation unit separated parts of said elongate metallic member issuing from said separation unit are free to move laterally with respect to said cutter.

48. (Twice Amended) A process for separating cold elongated metallic members along a substantially longitudinal axis thereof, said device comprising:

a separation unit having a cutter;

00

support means extending upstream and downstream of said separation unit to support said elongate member[, said support means extending in a direction substantially parallel to a longitudinal axis of said elongated member];

a feeder means to feed said elongate member towards and through said separation unit, said feeder means further comprising a pusher arm upstream of said separation unit, said pusher arm exerting a force on an end of said elongate metallic member distal from said separation unit to push said member towards and through the said separation unit; and

means to constrain lateral movement of said elongate metallic member passing through said separation unit, said constraining means further comprising at least one pair of horizontally spaced apart guide rollers, said guide rollers being freely rotatable about a substantially vertical axis, wherein downstream of said separation unit separated parts of said elongate metallic member issuing from said separation unit are free to move laterally with respect to said cutter, said process comprising the steps of:

placing said elongate member on said support means of said device;

aligning said substantially longitudinal axis of said elongate member with said cutter of said separation unit;

feeding said elongate member through said separation unit to cut said separate sections from said elongated member;

supporting said separated sections of said elongated member; and constraining lateral movement of said elongate member in said separation unit.